

ENGINE-DRIVEN

MAGIC WELD 150A

The **MAGIC WELD 150** is the best in its class for duty cycle and weight. It is a light-weight, 150-Amp DC Stick welder, built for everyday use as a welder or as a portable generator. It is paired with an outstanding Honda GX 200 four stroke engine for a powerful and steady arc. The engine includes an auto idle feature to increase fuel efficiency and engine life. The entire unit's 75 lbs. (34 kg) weight and 150A in 60% duty cycle, makes it a breeze to use out on site or around the farm. This welder is equipped with a "Power Optimizer" function, designed and patented by MOSA. This is a special feature aimed at preventing engine overload when working near its power limit.

FEATURES

- 150 A in 60% Duty Cycle, only weighing 75 lbs. (34 kg).
- DC arc welding machine.
- High-frequency voltage control and welding current.
- Welding with all types of electrodes including cellulosic electrodes.
- Auxiliary current AC with micro-breaks for protection.
- Engine stop for low oil level (oil alert).
- Economizer function.
- Power optimizer (Patented by MOSA).
- CE certificated.
- Engine meets U.S. EPA and California EXH/EVP SORE Regulations.
- Auto Idle.
- Permanent magnet alternator, self-excited, brushless.
- Honda GX 200 Engine.



MAGIC WELD 150A Technical Specification

Process	Stick Electrode
D.C Welding (Constant Current)	
Welding Current Range	30-150 A
Duty Cycle @ Maximum Welding Current in 104° F (40° C)	60% (150 A)
Open Circuit Voltage : Volt	72 V
D.C. GENERATION, 60 Hz - Permanent magnet alternator, self-excited, brushless	
Single Phase Auxiliary Power (Max)	1.5 KVA (110 V /13.6 A)
Insulation Class	H
ENGINE- Gasoline, 4- stroke, OHV, Air cooled	
Model	Honda GX 200
* Output Max	5 KW (6.7 HP)
Cylinder / Displacement	1/196 cm ³
Fuel Consumption (Welding 60% DT)	1.1 l/h
* Minimum output(not overloadable) according to SAE J 1349	
Environmental Protection Approval :	
Engine meets U.S. EPA and California EXH/EVP SORE Regulations	
General Specification	
Tank Capacity	3.1 l
Running Time (welding 60%)	3 h
IP protection Degree	IP 23
*Dry Weight : lb (Kg)	75 lb (34 Kg)
Dimensions Including Handle (D,W,H) : inch (mm)	24.4 x 19.5 x 21.3 inch (620 x 495 x 540 mm)
*Weight is without trolley	

CANAWELD RESERVES THE RIGHTS OF CHANGING THE SPECIFICATION WITHOUT NOTICE

Available Models :

MAGIC WELD 150A (C0CD60E12)

Magic Weld 150A Including Trolley (C0CD60E0T)

What Is Included

MAGIC WELD 150A

ITEM	PART NO.	
* MAGIC WELD 150A	C0CD60E12	
* Magic Weld 150A Including Trolley	C0CD60E12T	
Welding Cable Connectors Dinse Style	CWMC3570/P2	

* Please select your preferences



OPTIONAL ACCESSORIES

PRODUCT	PART NO.	
Welder Cart Magic Weld 150	CWM222700131	
Ground Clamp	ALP1980449	
Electrode holder	ALP2280095	